

Varspan Sleaving

Expandable Polyester Monofilament Sleaving

(-70°C to +125°C) (-94°F to +257°F)

Expandable Halar® Monofilament Sleaving

(-70°C to +150°C) (-94°F to +302°F)

Description

Varspan expandable monofilament sleeveings are designed to provide mechanical protection to wires, cables, harnesses, hydraulic lines, tubes, hoses, etc., as well as to components of both regular and irregular shapes. Their ability to expand to two or three times their original ID allows for ease of application and their “open-weave” braid construction, which will not trap heat or moisture, results in a cost-effective bulk/weight ratio.

Varspan is available as an expandable polyester monofilament sleeveing in three types, or as an expandable Halar® E-CTFE (ethylene chlorotrifluoroethylene) monofilament sleeveing.

Varspan expandable sleeveing made with polyester monofilaments is offered in both general-purpose (Varspan GP) and flame-retardant (Varspan FR) yarns. The general-purpose version is also available in heavy duty (Varspan HD), which is braided with a thicker .015" diameter monofilament strand for applications where additional abrasion and cut-through protection is required. All exhibit good mechanical, chemical and thermal stability in a temperature range of -70°C to +125°C.

Varspan GP and Varspan HD are UL Certified under UL File #E491276.

Varspan HT expandable sleeveing is made with Halar® E-CTFE monofilaments and, in addition to being flame retardant, offers superior resistance to most solvent acids and bases. Varspan HT can be used at higher operating temperatures (-70°C to +150°C) than Varspan GP, FR, and HD sleeveings.

Cut with a hot-blade device for frayless ends or turn ends inward.

Applications

All Varspan sleeveings are suitable for military, industrial, marine, aeronautical, transportation, electronic, and manufacturing applications where mechanical protection and resistance to chemicals, jet fuel, diesel fuel, gasoline, lubricating oils, solvents, hydraulic fluids, water and salt water are prerequisites and flexibility through a wide range of operating temperatures is desired.

Varspan FR offers a higher degree of flame retardation required for special applications.

Varspan HT (Halar®) in addition to flame retardation and its suitability for use at higher operating temperatures than the other Varspan sleeveings, is recommended for use where the sleeveing may be exposed to harsher chemicals and more severe environments.

Sizes and Colors

Varspan GP - 1/16" through 3" I.D. Available in all colors including clear; also available in color combinations/patterns.

Varspan FR - 1/8" through 2-1/2" I.D. Black or natural (white), with the FR identified by a criss-cross (diamond) pattern of two contrasting tracer strands.

Varspan HD - 3/8" through 3" I.D., Black color only

Varspan HT (Halar®) - 1/8" through 2-5/8" I.D. Black or natural (white), identified by one contrasting tracer strand

Standard Packaging

Spools. See reverse side for details

®Halar is a registered trademark of Solvay Solexis S.p.A.

Varspan Sleeving Typical Properties

Nominal Size (inches)	Min-Max Expansion (inches)	Weight (lb/100ft)	Standard Spool Length (ft.)
-----------------------	----------------------------	-------------------	-----------------------------

Varspan GP and Varspan FR (average strand diameter .010")

1/16 (GP only)	3/64 – 5/32	0.12	1,000
1/8	1/16 – 3/16	0.18	1,000
1/4	1/8 – 3/8	0.27	1,000
1/4 (3-end, GP only)	1/8 – 5/16	0.37	1,000
3/8	3/16 – 1/2	0.57	500
1/2	1/4 – 3/4	0.74	500
5/8 (GP only)	3/8 – 1-1/4	0.99	250
3/4	1/2 – 1-1/4	1.25	250
1 and 1-1/4	3/4 – 1-5/8	1.59	250
1-1/2	1 – 2-1/8	1.96	250
1-3/4	1-1/4 – 2-1/4	2.63	200
2	1-3/4 – 3-1/2	3.43	200
2-1/2	1-7/8 – 3-3/4	3.75	100
3 (GP only)	2-1/2 – 4	3.79	100

Varspan HD (average strand diameter .015")

3/8	3/16 – 1/2	0.83	500
5/8	5/16 – 7/8	1.14	500
1	1/2 – 1-1/4	1.74	250
1-1/2	1 – 2-1/2	2.57	250
2	1-1/2 – 3	3.48	100
3	2 – 4	4.35	50

Varspan HT (Halar®) (average strand diameter .010")

1/8	3/32 – 1/8	0.25	500
1/4	1/8 – 3/8	0.40	500
1/2	1/4 – 7/8	1.20	500
3/4	1/2 – 1-1/4	1.70	250
1	1/2 – 1-3/8	2.30	250
1-1/4	3/4 – 1-1/2	2.80	250
1-7/8	1-1/4 – 2-1/2	4.00	75
2-5/8	1-3/4 – 3-1/2	6.00	50

Note:

Information contained here is precise and reliable. However, being unique, each end-use should be evaluated to satisfy its specific requirements.



Electrical Insulating Sleeving

- 512 West Court Street, Rome, NY • www.varflex.com • e-mail: sales@varflex.com •
- Phone (315) 336-4400 • Fax (315) 336-0005 • Toll Free 1-800-648-4014 •